

**2.0-MP IR Bullet Network
POE Camera**



Feature

- 1/2.7"2 Megapixel High resolution CMOS
- H.264 Main Profile @ level 3.0 coding
- Support Color/BW mode converting
- Build in Motion Detection
- auto-retrieve function and auto-connection network
- Support Plug and play
- Integrated ONVIF standard

Model	UV-AHDBQ529
Hardware	
Sensor	1/3" CMOS Sensor
Resolution	1920X1080 2.0 MP
Lens	2.8/3.6/4/6MM Lens
IR LED	6 Pcs LED Array
Day/Night	IR-CUT
IR Distance	30 Meters
Min. Illumination	0.5lux; 0 lux with IR on
Max S/N Ratio	50dB
Video	
Compression	H.264
image	main stream: 2.0MP@30fps
Bit Rate	128~4096kbps, Supports CBR/VBR
Image Control	Hue, saturation, brightness, contrast, exposure
Auto Image Control	AE, AWB
Audio(Optional)	
Compression	G.711-A
Bit Rate	64kbps/128kbps
Talkback	support
Mobile phone	iPhone, iPad, Android
WIFI Encryption	WAP, WAP2
Interface	
Audio Input (Optional)	1 CH 3.5mm audio interface, MIC IN/LINE IN

Audio Output (Optional)	1 CH 3.5mm audio interface
General	
Working Temperature	-10°C~ +55°C
Working Humidity	0% - 90%
Protection Level	IP66 Rated Waterproof
Power Supply	DC 12 V/1.5A
Power Consumption	Maximum 6w
Approvals	UL, CE, FCC, RoHS, ISO

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

