

2.0MP IR Dome Network IP Camera



Feature

- ONVIF2.1 (1.02 backward Compatible)
- 1/3" CMOS Sensor 2.0 MP
- IR distance 30-50M
- Support P2P function
- Support H.264 (H.266) compression
- Support Alarm and Audio (Optional)
- IP 67 Water Proof
- POE (IEEE802.3af); 12 VDC Power Supply

| | |
|------------------------|---|
| Model | UV-AHDDP719 |
| Hardware | |
| Sensor | 1/3" CMOS Sensor |
| Resolution | 1920X1080 2MP |
| Lens | 2.8~12mm Varifocus Lens |
| IR LED | 42 LED |
| Day/Night | IR-CUT |
| Min. Illumination | 0.5lux; 0 lux with IR on |
| Max S/N Ratio | 50dB |
| Video | |
| Compression | H.264 |
| image | main stream: 2.0MP@30fps |
| Bit Rate | 128~4096kbps, Supports CBR/VBR |
| Image Control | Hue, saturation, brightness, contrast, exposure |
| Auto Image Control | AE, AWB |
| Audio(Optional) | |
| Compression | G.711-A |

| | |
|---|--|
| Bit Rate | 64kbps/128kbps |
| Talkback | support |
| Mobile phone | Iphone, ipad, Android |
| WIFI Encryption | WAP, WAP2 |
| Interface | |
| Audio Input(Optional) | 1 CH 3.5mm audio interface, MIC IN/LINE IN |
| Audio Output(Optional) | 1 CH 3.5mm audio interface |
| General | |
| Working Temperature | -10°C~ +55°C |
| Working Humidity | 0% - 90% |
| Protection Level | IP66 Rated Waterproof |
| Power Supply | DC 12 V/1.5A |
| Power Consumption | Maximum 6w |
| Approvals | CE , FCC, RoHS |
| <p>Unique VISION CCTV TECHNOLOGY</p> <p>Design & Specifications subject to change without prior notice.</p> <p>FCC CE (RoHS) ONVIF®</p> | |

Exclusive Distributon in Bangladesh

