

**2.0-MP IR Dome Network  
POE Camera**



**Feature**

- 1/2.7"2 Megapixel High resolution CMOS
- H.264 Main Profile @ level 3.0 coding
- Support Color/BW mode converting
- Build in Motion Detection
- auto-retrieve function and auto-connection network
- Support Plug and play
- Integrated ONVIF standard

Model	UV-IP DF420
<b>Hardware</b>	
Sensor	1/2.7"2.0 Megapixel high definition CMOS
Lens	2.8~12mm Varifocus Lens
IR LED	5 IR LEDS 24pcs, IR Distance 25-35m
POE	Poe is optional
Day/Night	IR-CUT
Min. Illumination	0.1lux; 0 lux with IR on
Max S/N Ratio	50dB
<b>Video</b>	
Compression	H.264
Image	main stream:1280x1080@1-25fps,1280x960@1-25fps sub stream:640x480@1-25fps,320x240@1-25fps
Rate	128~4096kbps, Supports CBR/VBR
Image Control	Hue, saturation, brightness, contrast, exposure
Auto Image Control	AE, AWB
<b>Audio(Optional)</b>	

Compression	G.711-A
Rate	64kbps/128kbps
Playback	support
Mobile phone	Iphone, ipad, Android
WiFi Encryption	WAP, WAP2

**Interface**

Audio Input( <b>Optional</b> )	1 CH 3.5mm audio interface, MIC IN/LINE IN
Audio Output( <b>Optional</b> )	1 CH 3.5mm audio interface

**General**

Working Temperature	-10°C~ +55°C
Working Humidity	0% - 90%
Protection Level	IP66 Rated Waterproof
Power Supply	DC 12 V/1.5A
Power Consumption	Maximum 6w
Approvals	CE , FCC, RoHS

Unique VISION CCTV TECHNOLOGY  
 Design & Specifications subject to change without prior notice.

FCC CE RoE ONVIF®

**Exclusive Distributon in Bangladesh**

