



2.0-MP IR Bullet Network POE Camera



Feature

- ONVIF 2.1(1.02 backward Compatible)
- 1/3" CMOS Sensor 2.0MP
- IR Distance 30-50M
- Support P2P function
- Support H.264 Compression
- Support Alarm and Audio (optional)
- IP 67 Weather Proof
- POE (IEEE802.3af);12VDC Power Supply

Model	UV-IPBP914
Hardware	
Sensor	1/3" CMOS Sensor
Resolution	1920X10802MP
Lens	2.8/3.6/6mm lens
IR LED	4pcs IR Array Led
Day/Night	IR-CUT
Min. Illumination	0.5lux; 0 lux with IR on
Max S/N Ratio	50dB
Video	
Compression	H.265
image	main stream: 1920x1080@1-15fps 1280x1080@1-25fps sub stream: 640x480@1-25fps 320x240@1-25fps
Bit Rate	128~4096kbps, Supports CBR/VBR
Image Control	Hue, saturation, brightness, contrast, exposure

Auto Image Control	AE, AWB
Audio(Optional)	
Compression	G.711-A
Bit Rate	64kbps/128kbps
Talkback	support
Network	
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP
Compliance	ONVIF 2.1(1.02 backward compatible)
PC Client and Browser	ISS, IE6.0 and above
Mobile phone	Iphone, ipad, Android
WIFI Encryption	WAP, WAP2
Interface	
Audio Input(Optional)	1 CH 3.5mm audio interface, MIC IN/LINE IN
Audio Output(Optional)	1 CH 3.5mm audio interface
LAN	1 RJ45 10M/100M Ethernet port
General	
Working Temperature	-10°C~ +55°C
Working Humidity	0% - 90%
Protection Level	IP66 Rated Waterproof
Power Supply	DC 12 V/1.5A

Power Consumption	Maximum 6w
Approvals	CE , FCC, RoHS

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

