



odel	UV-IPDP315
rdware	
nsor	1/3" CMOS Sensor
solution	2048X1536 3.0MP
ns	2.8/3.6/6mm lens
LED	6 pcs IR Array Led
y/Night	IR-CUT
n. Illumination	0.5lux; 0 lux with IR on
ax S/N Ratio	50dB
deo	
mpression	H.264
age	main stream: 3.0MP@25fps
Rate	128~4096kbps, Supports CBR/VBR
age Control	Hue, saturation, brightness, contrast, exposure
to Image Control	AE, AWB
dio(Optional)	
mpression	G.711-A

Rate	64kbps/128kbps
lkback	support
bile phone	Iphone, ipad, Android
FI Encryption	WAP, WAP2
terface	
dio Input**(Optional)**	1 CH 3.5mm audio interface, MIC IN/LINE IN
dio Output**(Optional)**	1 CH 3.5mm audio interface
neral	
orking Temperature	-10°C~ +55°C
orking Humidity	0% - 90%
otection Level	IP66 Rated Waterproof
wer Supply	DC 12 V/1.5A
wer Consumption	Maximum 6w
provals	CE , FCC, RoHS



Exclusive Distributon in Bangladesh

IEMS

QUALITY CONTROL APPROVED