

### 3.0-MP IR Dome Network POE Camera



**Feature**

- ONVIF 2.1(1.02 backward Compatible)
- 1/3" CMOS Sensor 3.0MP
- IR Distance 30-50M
- Support P2P function
- Support H.264 Compression
- Support Alarm and Audio (optional)
- IP66 Rated Waterproof
- POE (IEEE802.3af);12VDC Power Supply

Model	UV-IPDP412
<b>Hardware</b>	
Sensor	1/3" CMOS Sensor
Resolution	2592x1920 4/5MP
Lenses	2.8/3.6/6mm lens
LED	1pcs IR Array Led
Day/Night	IR-CUT
Min. Illumination	0.5lux; 0 lux with IR on
Max S/N Ratio	50dB
<b>Video</b>	
Compression	H.265
Image	main stream: 5.0/4.0MP@20fps sub stream: 3.0MP@30fps
Rate	128~4096kbps, Supports CBR/VBR
Image Control	Hue, saturation, brightness, contrast, exposure
Auto Image Control	AE, AWB
<b>Audio(Optional)</b>	

Compression	G.711-A
Rate	64kbps/128kbps
Playback	support
Mobile phone	Iphone, ipad, Android
WiFi Encryption	WAP, WAP2

**Interface**

Audio Input( <b>Optional</b> )	1 CH 3.5mm audio interface, MIC IN/LINE IN
Audio Output( <b>Optional</b> )	1 CH 3.5mm audio interface

**General**

Working Temperature	-10°C~ +55°C
Working Humidity	0% - 90%
Protection Level	IP66 Rated Waterproof
Power Supply	DC 12 V/1.5A
Power Consumption	Maximum 6w
Approvals	CE , FCC, RoHS

Unique VISION CCTV TECHNOLOGY  
 Design & Specifications subject to change without prior notice.

FCC CE RoE ONVIF®

**Exclusive Distributon in Bangladesh**

