

2.0MP IR Dome Network IP Camera



Feature

- ONVIF2.4
- IR distance 20M
- Support P2P function
- Support H.264 (H.266) compression
- Support Alarm and Audio (Optional)
- IP 67 Water Proof
- 1/2.7 "CMOS, 2.0MP, 1080P
- 12VDC Power Supply

| | |
|------------------------|---|
| Model | UV-IPDP618 |
| Hardware | |
| Sensor | 1/3" CMOS Sensor |
| Resolution | 1920X10802MP |
| Lens | 2.8/3.6/ 4/6mm lens |
| IR LED | 24 LED |
| Day/Night | IR-CUT |
| Min. Illumination | 0.5lux; 0 lux with IR on |
| Max S/N Ratio | 50dB |
| Video | |
| Compression | H.264 |
| image | main stream: 2.0MP@30fps |
| Bit Rate | 128~4096kbps, Supports CBR/VBR |
| Image Control | Hue, saturation, brightness, contrast, exposure |
| Auto Image Control | AE, AWB |
| Audio(Optional) | |

| | |
|---------------------------------|---|
| Compression | G.711-A |
| Bit Rate | 64kbps/128kbps |
| Talkback | support |
| Network | |
| Protocol | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP |
| Compliance | ONVIF 2.1(1.02 backward compatible) |
| PC Client and Browser | ISS, IE6.0 and above |
| Mobile phone | Iphone, ipad, Android |
| WIFI Encryption | WAP, WAP2 |
| Interface | |
| Audio Input(Optional) | 1 CH 3.5mm audio interface, MIC IN/LINE IN |
| Audio Output(Optional) | 1 CH 3.5mm audio interface |
| LAN | 1 RJ45 10M/100M Ethernet port |
| General | |
| Working Temperature | -10°C~ +55°C |
| Working Humidity | 0% - 90% |
| Protection Level | IP66 Rated Waterproof |
| Power Supply | DC 12 V/1.5A |
| Power Consumption | Maximum 6w |
| Approvals | CE , FCC, RoHS |

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

