

**2.0MP IR Bullet Network POE Camera**



**Feature**

- ONVIF2.1 (1.0.2 backward Compatible)
- 1/3" CMOS Sensor 2MP
- IR distance 30-50M
- Support P2P function
- Support H.264 compression
- Support Alarm and Audio (Optional)
- IP 66 Water Proof
- POE (IEEE802, 3af); 12VDC Power Supply

Model	UV-IPDP703
<b>Hardware</b>	
Sensor	1/3" CMOS Sensor
Resolution	1920X10802MP
Lens	2.8~12mm Varifocus Lens
IR LED	42 LED
Day/Night	IR-CUT
Min. Illumination	0.5lux; 0 lux with IR on
Max S/N Ratio	50dB
<b>Video</b>	
Compression	H.264
image	main stream: 2.0MP@30fps
Bit Rate	128~4096kbps, Supports CBR/VBR
Image Control	Hue, saturation, brightness, contrast, exposure
Auto Image Control	AE, AWB
<b>Audio(Optional)</b>	

Compression	G.711-A
Bit Rate	64kbps/128kbps
Talkback	support
<b>Network</b>	
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP
Compliance	ONVIF 2.1(1.02 backward compatible)
PC Client and Browser	ISS, IE6.0 and above
Mobile phone	Iphone, ipad, Android
WIFI Encryption	WAP, WAP2
<b>Interface</b>	
Audio Input( <b>Optional</b> )	1 CH 3.5mm audio interface, MIC IN/LINE IN
Audio Output( <b>Optional</b> )	1 CH 3.5mm audio interface
LAN	1 RJ45 10M/100M Ethernet port
<b>General</b>	
Working Temperature	-10°C~ +55°C
Working Humidity	0% - 90%
Protection Level	IP66 Rated Waterproof
Power Supply	DC 12 V/1.5A
Power Consumption	Maximum 6w
Approvals	CE , FCC, RoHS

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

