

2.0MP IR Dome Network IP Camera



Feature

- ONVIF2.4
- IR distance 20M
- Support P2P function
- Support H.264 (H.266) compression
- Support Alarm and Audio (Optional)
- IP 67 Water Proof
- 1/2.7 "CMOS, 2.0MP, 1080P
- 12VDC Power Supply

Model`	UV-POEIP525-M
Hardware	
Sensor	1/2.7" CMOS OV4689
Resolution	1920X1080P
Lens	2.8/3.6/ 4/6mm lens
Camera Type	Analog HD
IR LED	24 LED
Day/Night	IR-CUT
Min. Illumination	1.7 lx(F1.6?50 IRE?ICR OFF)?0.3 lx(F1.6?50 IRE?ICR ON)
Max S/N Ratio	50dB
Video	
Compression	H.264 (High Profile support)/H.265
image	main stream: 2.0MP@30fps
Bit Rate	128~4096kbps, Supports CBR/VBR
Image Control	Hue, saturation, brightness, contrast, exposure
Auto Image Control	AE, AWB
Audio(Optional)	

Compression	G.711-A
Bit Rate	64kbps/128kbps
Talkback	support
Network	
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP
Compliance	ONVIF 2.1(1.02 backward compatible)
PC Client and Browser	ISS, IE6.0 and above
Mobile phone	Iphone, ipad, Android
WIFI Encryption	WAP, WAP2
Interface	
Audio Input(Optional)	1 CH 3.5mm audio interface, MIC IN/LINE IN
Audio Output(Optional)	1 CH 3.5mm audio interface
LAN	1 RJ45 10M/100M Ethernet port
General	
Working Temperature	-10°C~ +55°C
Working Humidity	0% - 90%
Protection Level	IP66 Rated Waterproof
Power Supply	DC 12 V/1.5A
Power Consumption	Maximum 6w
Approvals	CE , FCC, RoHS

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

