

2.5MP IR Dome Network IP Camera



Feature

- 2.5" compact size, IR range reach up to 20 Meters
- Pan/Tit/Zoom A-B scan, tour available
- ONV IF2.4; Support P2P function
- Support H.264 (H.265) compression
- Support Audio (Optional)
- Competible with HIKVISION, DAHUA, XM, NVR
- Competible with Milestone and AXXON platform

Model	UV-IPPTZ04
Sensor	1/3" Cmos 4.0M AR0237
Resolution	HD:2048, 1920, 1080p/30fps /1080p/25fps
Rotation	Pan?355° Tilt?93 °
Pan speed	0-25°/s
Tilt speed	0-20°/s
Auto Flip	Support
Ration speed	Support
IR range	20 M
IR control	PWM
AB scan	Support, 0-355 degree
AB speed	1-9 grade selectable
Preset	220
Tour	3 groups (each group 16 preset?dwell time and speed selectable)
Calibration	support
Steam	triple streaming, 2 H.264 & 1 MJPEG or triple streaming, H.264+H.265 & 1 MJPEG
Lens	Fix lens 2.8/4/6/8/12 /vari focal lens2.8-8MM
Compression	H.264/H.265M-JPEG
Compression	G.711-A
Audio	1 audio (Optional)
Protocol	TCP/IP?HTTP? NTP?IGMP? DHCP?UDP?SMTP?RTP?RTSP?ARP?DDNS?DNS?PPPoE?P2P?

Compatibility	HIKVISION ,DAHUA, XM NVR , Milestone and AXON platform
Power	Power
Temperature	-15??+60?
Consumption	?10W
Thunder Proof	6000V
Size	137.5X110mm
Weight	N.W 0.36kg/G.W 0.53kg

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

