



Model	UV-HDPTZH09
IR distance	20m
Pan range and speed	Pan 355°endless rotate, speed 0?25°/S
Tilt range and speed	0°?90°, speed 0?20°/S
Preset	16
Patrol	1 group
Pattern	1 group
AB scan	Support
Park action	Support, can select preset, patrol, pattern, A.B scan
Resolution	2.0 MP 1920?H?X 1080?V
Sensor	1/2.9 Low illumination CMOS
Illumination	Color?0.2Lux@F2 Black?0.01Lux@F2
S/N	?41dB
Optical zoom	3X, 2.8 mm?8mm
Angle view	106.6°——51.8°
White balance	auto/manual
Exposure mode	auto/manual
BLC	Support
Gain control	Support
Electronic shutter	1/30s~1/10,000s
Digital WDR	Support

DNR	HIKVISION ,DAHUA, XM NVR , Milestone and AXXON platform
Power	2D/3D digital
Focus mode	auto/manual
Day night mode	Day night mode
Edge illumination compensation	Support
Video port	BNC port
Power port	DC 12V/1A
Consumption	10W( max)
Working temperature/Humidity	-20??+60???90%RH(frostless)
Protection Grade	TVS3000V lightning protection, surge protection and voltage transient protection

**Unique VISION CCTV TECHNOLOGY**

Design & Specifications subject to change without prior notice.



**Exclusive Distributor in Bangladesh**

