



NVR-N9616 POE



Feature

- Support for H. 265/H.264 encoding format Streaming access and decoding output
- Embedded LINUX operation system
- P2P cloud service
- Support ONVIF protocol
- Support sync video recording, playback Remote monitoring, backup
- Support monitor PTZ on preview mode
- Support megapixel HD network video preview

Model	NVR-N9616 POE
Operating System	Embedded LINUX operating system
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional
Dual Stream	Each channel can set main stream and sub stream
Video Standard	H.264
Monitoring Image Quality	4K / 5MP / 3MP / 1080P / 960P / 720P
Image Motion Detection	Each screen can set multiple detection areas and set 6-level sensitivity
Recording Playback Quality	Any 4ch 4K playback/ 9ch 5MP playback /16ch 1080 playback simultaneously
Region Cover	Every channel can set 4 cover regions?IPC Support?
Recording Mode	Support manual , auto, dynamic detection, alarm trigger record mode
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup ?Partly needs IPC Support?
Operation Way	Mouse, Keyboard
Local Login	Username and password
Recording Storage	Local HDD, network
Video Input	? 16x(3840*2160)+sub[960*576]+4Ref.+4Play ? ? 16x(2592*1944)+sub[960*576]+4Ref.+9Play ? ? 16x(1920*1080)+sub[960*576]+4Ref.+16Play
Audio Input	16ch network audio input
Video Output	1ch VGA+1ch HDMI
Audio Output	1ch RCA output
NetworkPort	1 RJ45,10M/100M/1000M self-adaptive LAN port
RS485 Port	Full duplex standard 485 port
POE Port	8 POE port
USBPort	1USB 3.0 port, 2 USB 2.0 ports

Alarm Input	4ch
Alarm Output	4ch
HDDPort	4×SATAHDDPort
MAX Capacity	Each port supports MAX 4TB HDD
Mobile Surveillance	Support( iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone
Power Supply	ATX110-220V 250W 50-60Hz
Power Consumption	?30W?without HDD?
Working Temperature	-10???55?
Working Humidity	10?-90?
Dimension	Equipment: 440mm×432mm×90mm, Packing: 539mm×550mm×225mm
Weight(without HDD)	N.W.: 7.4Kg; With Package: 9.8Kg
Outside Carton	2pcs / carton. 555mm×545mm×470mm; Weight: 21Kg
Installation Way	Desktop Installation

**Unique VISION CCTV TECHNOLOGY**

Design & Specifications subject to change without prior notice.



**Exclusive Distributon in Bangladesh**

