



Feature

- ONVIF 2.4
- Support HDMI 1080P output VGA HD output
- Support P2P function
- Support H.264/H.265 compression
- Support alarm and audio (optional)

Model	6016M
Main processor	Hi3536D
Operating System	Embedded Linux
System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Operator interface	16-bit true color graphic menu operation interface, support mouse operation
Preview	1/4/9/16
Video input(IP)	16*5M(15fps)/8*5M/16*1080P
Access bandwidth	64Mbps
Forwarding bandwidth	64Mbps
Video compression	H.265+/H.264
Display quality	Max:1920*1080 H.265
Playback quality	5M/1080P
Decode	1*5M/1*5M/2*1080P
VR	Unsupport
Motion detection	Support(depend on camera)
Audio compression	G.711A
Intercom	Support
Recording mode	Manual>Alarm>Dynamic Detection>Timing
Local playback	1*5M/1*5M/2*1080P
Search mode	Search by Time/Calendar/Event/Channel
Record storage	HDD?Network
Backup mode	Network backup, USB harddisk, USB burner, SATA burner
Video output	1ch VGA?1ch HDMI HD output

PowerConsumption	<10W(WithoutHDD)
Work environment	Temperature:0?25?,Humidity:10%?90%RH,Atm:86kpa?106kp
Network interface	1*RJ45 10M/100MAadaptiveEthernet port
USB interface	2*USB2.0ports
HDD	1 SATA(Up to8TB for eachdisk)
ONVIF	Support
Power supply	12V/2A

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

