

## 1.0mp/1.3mp/2.0mp Varifocal AHD IR Dome Camera



### Feature

- ONVIF 2.1(1.02 backward Compatible)
- 1/3" CMOS Sensor
- IR Distance 30-50M
- Support P2P function
- Support H.264 Compression
- Support Alarm and Audio (optional)
- IP66 Rated Waterproof
- POE (IEEE802.3af);12VDC Power Supply

|                                  |                                               |
|----------------------------------|-----------------------------------------------|
| Model                            | UV-AHDDX307                                   |
| Pick up Element                  | 1/4" H42 + NVR2431H                           |
| Effective Picture Elements (H×V) | 1280*720                                      |
| Horizontal Resolution            | 720P                                          |
| Min. Illumination                | 0.1Lux 0Lux (with IR LED ON)                  |
| Max S/N Ratio                    | More than 48dB                                |
| Scanning System                  | 2:1 interface                                 |
| Synchronous System               | Internal, Negative sync.                      |
| Auto Electronic Shutter          | NTSC: 1/60s~1/100,000s, PAL: 1/50s~1/100,000s |
| Gama Characteristic              | 0.45                                          |
| IR Distance                      | 15 Meters (with 18PCS Infrared LEDs)          |
| IR Status                        | Under 10Lux by CDS                            |
| IR Power On                      | CDS AUTO Control                              |
| Video Output                     | 1Vpp, 75?                                     |
| Auto Gain Control                | Auto                                          |
| Power/Current                    | DC12V/500mA                                   |
| Lens                             | 2.8~12mm Varifocus Lens                       |
| Dimension (mm)                   | 110(W)x90(H)mm                                |
| Weight (g)                       | 0.3kg                                         |
| Storage Temperature              | -30~+60?                                      |

Operating Temperature -10~+50?

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



**Exclusive Distributon in Bangladesh**

