



2.0-MP IR Dome Network POE



- Feature**
- ONVIF2.4
 - IR distance 20-30M
 - Support P2P function
 - Support H.264/H.265compression
 - Support alarm and audio (optional)
 - 1/2.7" CMOS, 2.0 MP, 1080 P
 - PoE (IEEE802.3af);12VDC Power Supply

Unique Vision

Model	UV – Promotional Dome
Country of Origin	China
Camera	
Sensor	1/2.7" CMOS OV4689
Effective Pixel	2.0 Megapixels
Resolution	1920x1080P@60fps
Aperture Value	F1.6~F3.5
Min. Illumination	1.7 lx(F1.6?50 IRE?ICR OFF)?0.3 lx(F1.6?50 IRE?ICR ON)
AGC Control	Manual/Auto
S/N Rate	?50db
White Balance	Manual/Auto
IR-cut	Manual/Auto
Communications Protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP
Compression	H.264 (High Profile support)/H.265
Frame rate	1920x1080P@60fps
Streaming	Dual-stream
Notify event	Email / FTP
Ethernet	RJ-45 10 / 100BASE-T
Security	Protected by password, filter IP
Protocol	IPv4, TCP/IP, UDP, HTTP, HTTPS, RTP, RTSP, " "DHCP, UPnP, FTP, SMTP, NTP, ARP,
Storage(optional)	SD card up-to 128GB

Mobile View(optional)	Android , iPhone
Menu	English
Pan and Tilt position display	Support
Baud Rate	1200/2400/4800/9600bps (Default is 9600bps)
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	?95% Non Condensing
Power Supply	DC12V 2A, POE
Lightning Protection	Transient voltage 6000V
IR parameters	
Auto Control IR LED	PWM
LEDs	2 Array
IR distance	Up to 30 to 50 meters
IR illumination on	1-15 grades selectable
Support ambient light detection	1-50 grades selectable

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

