




#### Feature

- ONVI 2.4
- Support HDMI 1080P output VGA HD output
- Support P2P function
- Support H.264/H.265 compression
- Support alarm and audio(optional)

Model	NVR6016M
System	
The main Processor	Hi3536D
The operating system	Embedded LINUX system
System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	
Operator interface	16-bit true color graphic menu operation interface, support mouse operation
Preview	1/4/9/16
Video	
Video input (IP)	16*5M(15fps)/8*5M/16*1080P
Access bandwidth	64Mbps
Forwarding bandwidth	64Mbps
Video compression	H.265+/H.264
Display quality	Max:1920*1080 H.265
Playback quality	5M/1080P
Decode	1*5M/1*5M/2*1080P
VR	Unsupported
Motion detection	Support(depend on camera)
Audio	
Audio compression	G.711A
Intercom	Support
Record & Playback	
Recording mode	Manual>Alarm>Dynamic Detection>Timing
Local payback	1*5M/1*5M/2*1080P
Search mode	Search by Time/Calendar/Event/Channel

<b>Record storage</b>	HDD, Network
<b>Backup mode</b>	Network backup, USB hard disk, USB burner, SATA burner
<b>External interface</b>	
<b>Video output</b>	1chVGA?1chHDMIHD output
<b>Audio I/O</b>	0/0
<b>Alarm I/O</b>	0/0
<b>Network interface</b>	1*RJ45 10M/100MAdaptiveEthernet port
<b>USB interface</b>	2*USB2.0ports
<b>HDD</b>	1 SATA (Up to8TB for each disk)
<b>ESATA</b>	No
<b>Serial interface</b>	No
<b>Others</b>	
<b>ONVIF</b>	Support
<b>Power supply</b>	12V/2A
<b>Power Consumption</b>	<10W (Without HDD)
<b>Work environment</b>	Temperature:0??55?,Humidity:10%?90% RH,Atm:86kpa?106kp
<div> <div> Unique VISION CCTV TECHNOLOGY </div> <div>  </div> </div> <div>Design &amp; Specifications subject to change without prior notice.</div>	

**Exclusive Distributon in Bangladesh**

