



**Feature**

- ONVI 2.4
- Support HDMI 1080P output VGA HD output
- Support P2P function
- Support H.264/H.265 compression
- Support alarm and audio(optional)

<b>Model</b>	<b>NVR6016M</b>
<b>System</b>	
<b>The main Processor</b>	Hi3536D
<b>The operating system</b>	Embedded LINUX system
<b>System resources</b>	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
<b>Interface</b>	
<b>Operator interface</b>	16-bit true color graphic menu operation interface, support mouse operation
<b>Preview</b>	1/4/9/16
<b>Video</b>	
<b>Video input (IP)</b>	16*5M(15fps)/8*5M/16*1080P
<b>Access bandwidth</b>	64Mbps
<b>Forwarding bandwidth</b>	64Mbps
<b>Video compression</b>	H.265+/H.264
<b>Display quality</b>	Max:1920*1080 H.265
<b>Playback quality</b>	5M/1080P
<b>Decode</b>	1*5M/1*5M/2*1080P
<b>VR</b>	Unsupported
<b>Motion detection</b>	Support(depend on camera)
<b>Audio</b>	
<b>Audio compression</b>	G.711A
<b>Intercom</b>	Support
<b>Record &amp; Playback</b>	
<b>Recording mode</b>	Manual>Alarm>Dynamic Detection>Timing
<b>Local playback</b>	1*5M/1*5M/2*1080P
<b>Search mode</b>	Search by Time/Calendar/Event/Channel

<b>Record storage</b>	HDD, Network
<b>Backup mode</b>	Network backup, USB hard disk, USB burner, SATA burner
<b>External interface</b>	
<b>Video output</b>	1chVGA?1chHDMIHD output
<b>Audio I/O</b>	0/0
<b>Alarm I/O</b>	0/0
<b>Network interface</b>	1*RJ45 10M/100MAadaptiveEthernet port
<b>USB interface</b>	2*USB2.0ports
<b>HDD</b>	1 SATA (Up to8TB for each disk)
<b>ESATA</b>	No
<b>Serial interface</b>	No
<b>Others</b>	
<b>ONVIF</b>	Support
<b>Power supply</b>	12V/2A
<b>Power Consumption</b>	<10W (Without HDD)
<b>Work environment</b>	Temperature:0??55?,Humidity:10%?90%RH,Atm:86kpa?106kp

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



**Exclusive Distributon in Bangladesh**

