



- Feature**
- ONVIF2.4
  - Support HDMI 1080P output VGA HD output
  - Support P2P function
  - Support H.264/H.265 compression
  - Support alarm and audio ( optional)

	Model	NVR-5004L
System	Main processor	Technical grade embedded microprocessor HI 3521A
	Operating system	Embedded LINUX operating system
	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation, USB back up.
Interface	Operation interface	16bit real color GUI interface support mouse operation
	Display screen	1/4/8 screen (take analog channel as an example, other is base on the selected channel mode)
Video	Video standard	PAL/NTSC
	Image encode	H.264(High Profile)?JPEG
	Monitor quality	4*5M(11FPS)/4*4M(15FPS)/4*3M(18FPS)/4*1080P(5in1)
	Playback quality	5M/4M/3M/1080P
	Decode capability	AHD:4*5M(11FPS)/4*4M(15FPS)/4*3M(18FPS)/4*1080P(5in1)
	Encode capability	AHD:4*5M(11FPS)/4*4M(15FPS)/4*3M(18FPS)/4*1080P(5in1)
	Multi-mode video input	AHD:4*5M(11FPS)/4*4M(15FPS)/4*3M(18FPS)/4*1080P(5in1) HVR:2*5M(AHD)+2*5M(IP)                      NVR:8*1080P+9*960P;4*3M;4*5M?
	Motion detection	Each channel can set 192?16*12?detection area?can set multi-level of flexibility (for local analog channel only)
Audio	Audio compression	G711A
	Bidirectional talk	support
Record and playback	Record mode	manual>alarm>motion detection>timing

Local playback	1-9ch playback synchronously (take local analog input for example, other is depended on the selected channel mode)	
Video search	time?date?event?channel search	
Storage and back up	Space occupation	Video?CIF 4~5G/day*channel? D1 16~20G/day*channel? audio?691.2M/day*channel
	Video storage	Local HDD ?Network
	Back up mode	Network backup?USB portable HDD?USB imprint?SATA imprint
Interface	Video input	8CH BNC(1.0Vp-p,75?)
	Video output	1CH VGA?1CH HDMI
	Audio input	4CH RCA
	Audio output	1CH RCA(200-3000mV,5K?)
	Alarm input	N/A
	Alarm output	N/A
	Network port	RJ45 10M/100M self-adaptive Ethernet port
	PTZ control	1 RS485?support multi kinds of PTZ protocol
	USB port	2*USB2.0
	HDD port	1 SATA ports?each max to 6TB?
	Wireless port	3G?WIFI(extension via USB port)
other	Power	12V/2A
	Consumption	<15W?not including HDD)
	Temperature	0?-255?
	Humidity	10% ?90%
	Atmosphere pressure	86kpa?106kpa

Dimension	L255*W220*H45MM
Weight	1.2KG

**Unique VISION CCTV TECHNOLOGY**

Design & Specifications subject to change without prior notice.



**Exclusive Distributon in Bangladesh**

