



### Technical parameter

Electric current: AC85V~264V/50-60HZ Power:  
<20W, low consume, low radiation Workplace  
environment: -20?~+45? Standard: ISO, CE  
Outer size: 2230\*835\*580mm Inner  
size: 1900\*700\*500mm Panel Material:  
Wood  
Net weight: 35 Kg

### Characteristic & Function:

**Portable** metal detector

**Program Self-diagnostic when power on**, automatically checking left and right door panel, LED light and choose the best working frequency.

Adopt advanced digital signal processing control replaced traditional analog signal control, better stability.

**Six mutual over-lapping detecting zones**, Simultaneous alarm from multi- zones;

**Sensitivity adjustable**: Each zone has 255 degree sensitivity level, three patterns: High, middle, Low for different requirements.

Preset the metal size, weight, volume, location to exclude the coin, key, belt.

**Sound Alarm**: 1-25s alarm times, 255 different sound volumes for choose

**LED light alarm**: LED bar graph on left and right door frame, visible alarm simultaneously to ascertain the layout of metal articles

**Automatically count passengers and alarm times**

**Password protection**, only the authorized person can operate.

**Anti-interference function**, using advanced interactive transmitting and receiving to avoid interference, frequency range from 4K-8K to avoid frequency interference

**Harmless to human body**: is harmless with heart peacemaker, pregnant women, magnetic floppy, recording tapes, etc.

### Application

The XYT2101A8 is designed for Airport, Customs, Railway station, Metro, Police, Court, Embassy, Commercial buildings, Military installations, Ships, Shipping Mall, Army, Prison, Government agency, Bank, Factory, Hotel, Entertainment

environments, Gymnasiums, Exhibition Centers etc. Public security.

**Exclusive Distributon in Bangladesh**

