



Technical parameter

Electric current: AC85V~264V/50-60HZ Power:
<20W, low consume, low radiation Net weight: 90KG

Workplace environment: -20?~+50?

Standard: GB15210-2003, CE

Standard External size: 2230mm(H)X835mm(W)X580mm(D) Standard

Internal size: 1990mm(H)X700mm(W)X500mm(D)

Characteristic & Function

- ? **Program Self-diagnostic when power on**, automatically checking left and right door panel, LED light and choose the best working frequency.
- ? **Six mutual over-lapping detecting zones**, Simultaneous alarm from multi- zones;
- ? **Sensitivity adjustable**: Each zone has 255 degree sensitivity level, three patterns: High, middle, Low for different requirements. Preset the metal size, weight, volume, location to exclude the coin, key, belt.
- ? **Sound Alarm**: 1-25s alarm time, 255 different sound volume for choose
- ? **LED alarm**: Six LED strip on the top control unit, indicate the alarm zones
- ? **Automatically count passengers and alarm times**
- ? **Password protection**, only the authorized person can operate.
- ? **Easy assembly: designed with only 2 pieces cables and 8 screws, Simply-to-follow instruction.**
- ? **Harmless to human body**: is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc.

Application

The XYT2101-II is designed for Airport, Customs, Railway station, Metro, Police, Court, Embassy, Commercial buildings, Military installations, Ships, Shipping Mall, Army, Prison, Government agency, Bank, Factory, Hotel, Entertainment environments, Gymnasiums, Exhibition Centers etc. Public security.

Exclusive Distributon in Bangladesh

