



Features

- *High resolution images
- *Simple User-friendly operation

*Strong image storage capacity

*Automatic Self-diagnostic maintenance system

*One Key shutdown control

Parameter

*Tunnel Size: 600mm (W)*400mm (H)

*Load Weight: 170Kgs

- *Conveyor Speed: 0.22m/s
- *Radiation Leakage: 0.10 μ G/h
- *Penetration: 40 mm steel
- *X-ray resolution: 40 AWG

X-Ray Generator

- *X-ray Beam Direction: From bottom
- *Beam Divergence: 80°
- *Tube Voltage: 80-160Kv
- *Electronic Current: 0.2-1.25mA
- *Cooling: Sealed oil cooling + 100% Duty cycle

Image Function

- *X-ray Converter Arrangement: Dual Energy L-shaped photodiode array detector
 - *Inorganic/Organic Stripping: Organic substances display in Orange, Inorganic substances display in blue, mixtures display in green.
 - *Maximum Image Resolution: 1024*768
 - *Image Storage: 100,000pcs
 - *Image Display Color: Black /White & Color
 - *Grey Level: 65536
 - *Zone & Zoom: 32 times zooming
- *Other Function: Alarm, Review, Density Enhancement, Negative/positive image, Light/Dark Enhancement, automatic count, One Key Power Off, Working status display, Date & time display, Rush Stop Protection, Dangerous Alarm, System Failure Alarm etc.

Exclusive Distributor in Bangladesh

