

2.0 MP IR Bullet network POE Varifocal



Feature

- ONVIF2.1 (1.02 backward Compatible)
- 1/3" CMOS Sensor 2.0 MP
- IR distance 30-50M
- Support P2P function
- Support H.264 (H.266) compression
- Support Alarm and Audio (Optional)
- IP 67 Water Proof
- POE (IEEE802.3af); 12 VDC Power Supply

Model	UV- IPBT716V
Country of Origin	China
Camera	
Sensor	1/2.7" CMOS OV4689
Effective Pixel	2.0 Megapixels
Resolution	1920x1080P@60fps
Lens	2.8MM - 12 MM
Aperture Value	F1.6~F3.5
Min. Illumination	1.7 lx(F1.6?50 IRE?ICR OFF)?0.3 lx(F1.6?50 IRE?ICR ON)
AGC Control	Manual/Auto
SN Rate	?50db
White Balance	Manual/Auto
Shutter	Manual/Auto
Communications Protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP
Compression	H.264 (High Profile support)/H.265/ H.265+
Frame rate	1920x1080P@60fps
Streaming	Dual-stream
Notify event	Email / FTP
Network	RJ-45 10 / 100BASE-T
Security	Protected by password, filter IP
Protocol	IPv4, TCP/IP, UDP, HTTP, HTTPS, RTP, RTSP, "DHCP, UPnP, FTP, SMTP, NTP, ARP,
Storage(optional)	SD card upto 128GB
Mobile View(optional)	Android , iPhone
Menu	English
Roll and Tilt position display	Support
Bandwidth Rate	1200/2400/4800/9600bps (Default is 9600bps)
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	?95% Non Condensing
Power Supply	DC12V 2A, POE
Lightning Protection	Transient voltage 6000V
IR parameters	
Control IR LED	PWM

Ds	36 Pcs
distance	Up to 30 to 50 meters
illumination on	1-15 grades selectable
pport ambient light detection	1-50 grades selectable

Unique VISION CCTV TECHNOLOGY

esign & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

