

**3.0MP IR Bullet Network
POE IP Camera**



Feature

- ONVIF2.4
- IR distance 20M
- Support P2P function
- Support H.264 (H.266) compression
- Support Alarm and Audio (Optional)
- IP 67 Water Proof
- 1/2.7 "CMOS, 2.0MP, 1080P
- 12VDC Power Supply

Model	UV-IPDP512 POE 265
Hardware	
Sensor	1/3" CMOS Sensor
Resolution	3.0 Mega Pixel
Lens	2.8/3.6/6mm Lens Optional
IR LED	2 PCS Array IR LEDs
Day/Night	IR-CUT
Min. Illumination	0.5lux; 0 lux with IR on
Max S/N Ratio	50dB
Video	
Compression	H.265
image	mainstream: 1920x1080@1-25fps sub-stream: 640x360@1-25fps 320x180@1-25fps
Bit Rate	128~4096kbps, Supports CBR/VBR
Image Control	Hue, saturation, brightness, contrast, exposure
Auto Image Control	AE, AWB

Audio(Optional)	
Compression	G.711-A
Bit Rate	64kbps/128kbps
Talkback	support
Network	
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP
Compliance	ONVIF 2.1(1.02 backward compatible)
PC Client and Browser	ISS, IE6.0 and above
Mobile phone	iPhone, iPad, Android
WIFI Encryption	WAP, WAP2
Interface	
Audio Input(Optional)	1 CH 3.5mm audio interface, MIC IN/LINE IN
Audio Output(Optional)	1 CH 3.5mm audio interface
LAN	1 RJ45 10M/100M Ethernet port
General	
Working Temperature	-10°C~ +55°C
Working Humidity	0% - 90%
Protection Level	IP66 Rated Waterproof
Power Supply	DC 12 V/1A
Power Consumption	Maximum 6w

Approvals

CE , FCC, RoHS

Unique VISION CCTV TECHNOLOGY

Design & Specifications subject to change without prior notice.



Exclusive Distributon in Bangladesh

